

LOW VOLTAGE HEAT SHRINKABLE KITS

Features and Applications

Suitable for low voltage (max 1kV), 2,3,4 and 5 core plastic and paper insulated, with and without armor, power cable.

- ▶ Kits for indoor & outdoor applications for a wide range of conductor cross sections are available.
- ▶ Joint kits include varieties sizes of medium wall tubing
- ▶ Termination kits consists of breakouts and medium wall heat shrinkable tubing.

Low Voltage Joint Kits

Joint types	Order number	Cable cross section (mm ²)
2-core cable straight joints	HLVJ 2A	10-16
	HLVJ 2B	25-50
	HLVJ 2C	70-120
	HLVJ 2D	150-240
3-core cable straight joints	HLVJ 3A	10-16
	HLVJ 3B	25-50
	HLVJ 3C	70-120
	HLVJ 3D	150-240
4-core cable straight joints	HLVJ 4A	10-16
	HLVJ 4B	25-50
	HLVJ 4C	70-120
	HLVJ 4D	150-240
	HLVJ 4F	300-400
5-core cable straight joints	HLVJ 5A	10-16
	HLVJ 5B	25-50
	HLVJ 5C	70-120
	HLVJ 5D	150-240

Low Voltage Termination Kits

Joint types	Order number	Cable cross section (mm ²)
2-core cable straight joints	HLVT 2A	10-16
	HLVT 2B	25-50
	HLVT 2C	70-120
	HLVT 2D	150-240
3-core cable straight joints	HLVT 3A	10-16
	HLVT 3B	25-50
	HLVT 3C	70-120
	HLVT 3D	150-240
4-core cable straight joints	HLVT 4A	10-16
	HLVT 4B	25-50
	HLVT 4C	70-120
	HLVT 4D	150-240
	HLVT 4F	300-400



MEDIUM VOLTAGE HEAT SHRINKABLE TERMINATIONS

Features and Applications

- » Suitable for medium voltage , single and 3 core XLPE & PILC armoured & unarmoured power cable
- » Kits for indoor & outdoor applications for a wide range of conductor cross sections are available.
- » Termination kits include non-tracking, weather resistant tubing, insulation tubing ,stress control tubing, rainsheds and sealing mastic.

11KV(8.7/17.5) and 22 KV Terminations

Termination types	11KV(8.7/17.5) Termination Kits	22KV Termination Kits	Size of conductor (mm ²)
	Order number	Order number	
Single core XLPE cable indoor terminations	HIT11K 1A	HIT22K 1A	25-50
	HIT11K 1B	HIT22K 1B	70-120
	HIT11K 1C	HIT22K 1C	150-240
	HIT11K 1D	HIT22K 1D	300-400
3-core XLPE cable indoor terminations	HIT11K 3A	HIT22K 3A	25-50
	HIT11K 3B	HIT22K 3B	70-120
	HIT11K 3C	HIT22K 3C	150-240
	HIT11K 3D	HIT22K 3D	300-400
3-core XLPE cable outdoor terminations	HOT11K 3A	HOT22K 3A	25-50
	HOT11K 3B	HOT22K 3B	70-120
	HOT11K 3C	HOT22K 3C	150-240
	HOT11K 3D	HOT22K 3D	300-400
Single core PILC cable outdoor terminations	HOT11K 1A		25-50
	HOT11K 1B		70-120
	HOT11K 1C		150-240
	HOT11K 1D		300-400
3-core PILC cable Indoor terminations	HPIT11K 3A		25-50
	HPIT11K 3B		70-120
	HPIT11K 3C		150-240
	HPIT11K 3D		300-400
3-core PILC cable outdoor terminations	HPOT11K 3A		25-50
	HPOT11K 3B		70-120
	HPOT11K 3C		150-240
	HPOT11K 3D		300-400

36 KV Terminations

Termination types	Order number	Cable cross section (mm ²)
Single core XLPE cable indoor terminations	HIT36K 1A	25-50
	HIT36K 1B	70-120
	HIT36K 1C	185-240
	HIT36K 1D	300-400
Single core XLPE cable outdoor terminations	HOT36K 1A	25-50
	HOT36K 1B	70-120
	HOT36K 1C	150-240
	HOT36K 1D	300-400
3-core XLPE cable indoor terminations	HIT36K 3A	25-50
	HIT36K 3B	70-120
	HIT36K 3C	150-240
	HIT36K 3D	300-400
3-core XLPE cable outdoor terminations	HOT36K 3A	25-50
	HOT36K 3B	70-120
	HOT36K 3C	150-240
	HOT36K 3D	300-400