



Self-Contained Emergency KELUAR Sign

Slimline Design (Super bright LEDs)

PEX-138-LED
PEX-138R-LED

PEX-138-LED Surface Mount



PEX-138R-LED

Recess Mount

Specifications

Model	➡ PEX-138LED / PEX-138R-LED.
Mode	➡ Maintained.
Weight	➡ ~2.8 Kg (surface) / ~3.0 Kg (recess).
Battery	➡ 2 x 1.2V 1.6AH Ni-MH.
Housing	➡ Electro-galvanised sheet steel with powder coated paint.
Charger	➡ Constant current.
Mounting	➡ Surface mount to wall or ceiling / Ceiling recess mount.
Dimension	➡ 600 mm (L) x 66 mm (W) x 274 mm (H). 651 mm (L) x 60mm (W) 283 mm (H).
Monitoring	➡ Red LED indicator for charging.
Compliance	➡ MS 983 : 2004, MS 619 : Part 102 : Sect. 102.22 : 1985 (P). MS IEC 60598-1 : 2006. Jabatan Bomba Dan Penyelamat Malaysia certified.
Light Source	➡ 18 nos super bright LED (SMD).
Input Voltage	➡ 240 V +/- 10% 50/60 Hz.
Recharge Period	➡ 16 - 24 Hours.
Back Up Duration	➡ 3 Hours.
Battery Protection	➡ Low voltage cut-off to prevent over discharging.
Power Consumption	➡ < 5W.
Ingress Of Protection	➡ IP - 20.
Operating Temperature	➡ 0 °C to 65 °C.