



PEX-215LED

Self-Contained Emergency KELUAR Sign



PEX-215LED (Super Bright LEDs)



Specifications

Model	➔	PEX-215 LED.
Mode	➔	Maintained.
Weight	➔	~1.2 Kg.
Battery	➔	2 x 1.2V 1.6AH Ni-MH.
Housing	➔	Electro-galvanised sheet steel with powder coated paint.
Charger	➔	Constant current.
Mounting	➔	Surface mounting direct to wall or ceiling.
Dimension	➔	556mm (L) x 52mm (W) x 155mm (H).
Monitoring	➔	Red LED indicating healthy supply and charging.
Compliance	➔	MS 983 : 2004, MS 619 : Part 102 : Sect. 102.22 : 1985 (P). MS IEC 60598-1 : 2006. Jabatan Bomba Dan Penyelamat Malaysia certified.
Light Source	➔	18 nos super bright LED (SMD).
Input Voltage	➔	240 V +/- 10% 50Hz.
Recharge Period	➔	16 - 24 hours.
Back Up Duration	➔	3 hours.
Battery Protection	➔	Low voltage cut-off to prevent over discharging.
Power Consumption	➔	< 5W.
Ingress Of Protection	➔	IP-20.
Operating Temperature	➔	0 °C to 65 °C.



Note : Due to continuous development and improvement, our company reserves the right to change specifications without notice.