



PTH-311

Self-Contained Emergency Luminaire

PTH-311 (1.0W Power LED)



Specifications

Model.....	➤ PTH-311.
Mode.....	➤ Non-maintained.
Weight	➤ 320 grams.
Battery.....	➤ 2.4V 1.7AH Ni-cad.
Housing	➤ Injection moulded fire retardant, UV stabilize ABS Housing.
Charger.....	➤ Constant Current.
Mounting	➤ Recess mounted on ceiling.
Dimension.....	➤ 75 mm (L) x 88 mm (W) x 95 mm (Diameter).
Monitoring	➤ Green / Red LED "ON" to indicate charging. Equipped with push test switch to simulate power failure.
Compliance	➤ SIRIM MS 619-2-22:2005. MS IEC 60598-1:2012. Jabatan Bomba dan Penyelamat Malaysia certified.
Light Source.....	➤ 1.0W high lumen output LED.
Input Voltage	➤ 240V +/- 10% 50Hz.
Recharge Period	➤ 16 - 24 Hours.
Back Up Duration	➤ 3 Hours.
Battery Protection.....	➤ Low voltage cut-off to prevent over discharging.
Power Consumption.....	➤ < 5W.
Ingress of Protection.....	➤ IP - 20.
Operating Temperature	➤ 0 °C to 65 °C.
Lumen	➤ 152.50 lm
Power	➤ 4.584 W
C.C.T	➤ 5892
C.R.I	➤ 74